

DS-425

Weighing scale



**High precision weighing scale
with user-friendly features,
designed for a variety of
applications**



DS-425

Weighing scale

Accurate, fast, functional and easy to use



Counting function

Selectable weight units (g, kg, oz or lb.)

Check weighing with filling function



Backlight LCD

- **High display resolution: 1/30,000, resolution to 0.01g**
- **Standard RS-232C I/F** • **Digital tare subtraction**

Specifications

Capacity and resolution

Capacity	Resolution	Tare range	Platter size
Max 300g	e=0.01g	T=-150.00g	105 × 160mm
Max 3kg	e=0.1g	T=-1500.0g	205 × 250mm
Max 15kg	e=0.5g	T=-7500.0g	205 × 250mm

Dimensions: 256(W) × 321(L) × 80(H) mm / 10.08(W) × 12.64(L) × 3.15(H) inch

Internal resolution: 1/300,000
 Display resolution: 1/30,000
 Weight sensor: Load cell
 Weight display: 5 digits
 Power source: AC adapter (18VDC, 120mA)
 Power consumption: 2 W
 Operating temperature: 5°C to 35°C / 41°F to 95°F
 Operating humidity: 85%RH Max. (Non-condensing)
 Net weight: 3.5 kg / 7.71 lb
 Standard RS-232C I/F with Din 8 pin connector

** Specifications are subject to change without notice.*



230 W. Coleman St. • Rice Lake, WI 54868
 TEL: 715-736-0002 • FAX: 715-234-6967
www.digiscales.com