



Precision Balance

- Multiple Weighing Units
- Percentage, Counting







Model	NJW-300	NJW-600	NJW-1500	NJW-3000
Capacity	300 g	600 g	1500 g	3000 g
Readability	0.01 g	0.02 g	0.05 g	0.1 g
Divisions	30,000	30,000	30,000	30,000
Weighing Units / Functions	g / oz / lb / ct / dram / gn (UK) / oz t / dwt / mommes / taels (China) / taels (Taiwan) / troy taels / tola (India) / % / counting			
Linearity (g) (±)	0.02	0.04	0.1	0.2
Repeatability (g) (Std Dev)	0.02	0.04	0.1	0.2
Tare Range	To capacity by subtraction			
Power Source	4 x C type batteries (not included) or external power adapter (included)			
Construction	Stainless steel pan and ABS housing			
Display	0.5 inch (13 mm) wide viewing angle LCD with back light			
Pan Size (w x d)	4.33 inches / 110 mm diameter		5.5 x 6.7 inches / 140 x 170 mm	
Dimensions (w x h x d)	7.1 x 4.9 x 7.87 inches /	180 x 125 x 200 mm	7.1 x 2 x 7.87 inches / 180 x 50 x 200 mm	
Operating Environment	32° ~ 104° F non condensing R.H. \leq 85%			
Net Weight	2.7 lb (1.22 kg)		2.73 lb (1.24 kg)	
Shipping Weight	5.51 lb (2.5 kg)		5.29 lb (2.4 kg)	
Options	RS232C interface			

Features

Low profile, compact size
Reads in multiple weighing units and functions
Counting function
Percent function
Wind shield on 300 and 600 g models
Battery powered. External power adapter included
Zero tracking
Automatic power save
Low battery indicator
Auto-calibration function
Adjustable feet (spirit level on 300 g and 600 g models)

Wide angle LCD display and backlight

Dust cover

Benefits

Uses less counter space
Flexibility of operation
Enables counting of components and small parts
Allows for formulation preparation
Protects against drafts, ensuring stability of reading
Portability - battery lasts a minimum of 100 hours (without back light)
Assures that you always start weighing at zero
Conserves battery power

Conserves battery power
Alerts you to charge the battery, saving downtime
Ensures accuracy
Balance remains level for accurate results on
uneven working surfaces - Anti-slip
Can be seen from a wide viewing range
and in poor lighting conditions
Keeps scale clear from contamination

7.87"

SOLD BY:



Fast \square Affordable \square Quality Repairs