



1000111010101100100011110001000001111000100

digital perfection

**NEW**



## Electronic Cash Register

**DP-55**  
**DP-55 Plus**



## Specification

|  | DP-55  | DP-55 Plus  |
|--|--|---|
| Capacity of the items database         | up to 9999   | up to 30 000  |
| Item name length                       | up to 22 characters  |   |
| Maximal Sold quantity of one item      | up to 99 999,999 kg  |   |
| Barcode types                          | EAN-13, EAN-8, UPC, Barcode from a scale labels  |   |
| Tax type                               | VAT, up to 8 tax groups  |   |
| Stands                                 | up to 10   | up to 99  |
| Departments                            | up to 10   | up to 99  |
| Number of operators                    | up to 30 (of which 2 active)   | up to 30 (of these 30 active)   |
| Maximal number of sales in one receipt | more than 150  | more than 300 sales   |
| Types of service                       | <ul style="list-style-type: none"> <li>• Control of store exit</li> <li>• ECR which serves one stand</li> <li>• Waiter service</li> </ul>  |   |
| Types of payment                       | <ul style="list-style-type: none"> <li>• Cash, check, card, credit</li> <li>• Cash with alternative currency: USD or EUR</li> </ul>  |   |
| Fiscal memory                          | Non-volatile, can keep up to 2400 reports  |   |
| Journal                                | Stored in an EJ card or with postponed printing  | Recorded stored in a SD (EJ) card (up to 2 mln. lines)  |
| Thermal printer type                   | MLT4280KS-P1   |   |
| Printer speed                          | 12 lines/sec   |   |
| Graphical logo                         | Supported size 384x96 dots   | Supported size 384x96 dots (384x336 dots)   |
| Consumable - thermal paper             | <ul style="list-style-type: none"> <li>• Paper width 2x28 mm, thickness 60-72µm, roll diameter up to 65 mm</li> <li>• Paper width 57 mm, thickness 60-72µm, roll diameter up to 65 mm</li> </ul> |   |
| Operator's display                     | LCD 2 lines x 16 characters  | Graphic LCD, up to 4 lines and up to 22 char/line   |
| Customer's display                     | Alpha-numeric LCD 2 lines x 16 characters  |   |
| Power supply                           | AC 110-240V 50-60 Hz DC 12V 2500mA   |   |
| Li-Ion battery                         | Yes  | Option  |
| Clock/calendar                         | Stores information for at least 90 days after switching off the ECR  |   |
| Interface and additional device        | <ul style="list-style-type: none"> <li>• 1 x RS 232C</li> <li>• Scale support</li> <li>• BCR connection</li> <li>• Drawer support</li> </ul>   | <ul style="list-style-type: none"> <li>• 1 x Ethernet for local network connection</li> <li>• 1 x Drawer output</li> <li>• 2 x RS-232C for: barcode reader, scale, external customer display, bank terminal, PC</li> <li>• Interface for external keyboard</li> </ul> |
| GPRS                                   | Option   | External or Built in  |
| Working temperature                    | from 0°C to +45°C  |   |
| Dimensions (L x H x W), mm             | 220 x 70 x 166   |   |
| Weight, kg                             | 0.900 (with 1 paper roll)  |   |