



1000111010101100100011110001000001111000100

digital perfection



Mobile Thermal Printer

DPP-350






1000111010101100100011110001000001111000100

digital perfection



Specification

DPP-350	
Printing Method	Line Thermal Printing
Total Dots	576 dots / line
Dot Density	8 dots / mm (203 dpi)
Print Speed	60 mm / sec
Print Width Characters per Line	72 mm Font A: 48 characters / line Font B: 64 characters / line Font C: 48 characters / line (loadable) Font D: 64 characters / line (loadable)
Recommended Paper	<ul style="list-style-type: none"> Thermal Paper Roll: <ul style="list-style-type: none"> - 78 mm / Ø 50 mm, thickness 60 µm; - 80 mm / Ø 50 mm, thickness 60 µm; - 57 mm / Ø 50 mm, thickness 60 µm. Label Paper Roll: <ul style="list-style-type: none"> - 78 mm / Ø 50 mm; - 57 mm / Ø 50 mm.
Interfaces	<ul style="list-style-type: none"> • RS-232C with optional special cable (1200 – 115200 bps); • USB 1.1 compatible 2.0 host / slave; • Bluetooth (option) ; • Wi-Fi (option).
Drivers for	<ul style="list-style-type: none"> • Pocket PC; • Palm OS; • Windows; • BlackBerry.
Configuration options	<ul style="list-style-type: none"> • Magnetic Stripe Reader (option); • Smart Card Reader (option); • Mi FARE Reader (option); • SD Card Slot for SD Card or Wi-Fi Modules (option).
Emulation	ESC/POS / LABEL <ul style="list-style-type: none"> • Label Printing ELTRON compatible (EPL-2); label length 100 mm maximum; • Barcode Printing: EAN13, EAN8, UPC-A, UPC-E, Codabar, Code 39, Code 128.
Power Supply	Rechargeable battery (Li-Ion 7.4V; 2000 mAh)
Battery Charge Time	3 hours maximum
Print Lines per Charge	30,000 (fully charged)
Buffer	<ul style="list-style-type: none"> • ESC/POS mode: 56 Kb; • Label mode: 16 Kb.
Reliability	50,000,000 pulses or 50 km mechanism (MCBF): 15,000,000 lines
Weight	340 grams (w / o paper); 430 grams (with paper); 540 grams (with label paper roll).
Dimension (w) x (d) x (h), mm	108 x 111 x 62
Environment	<ul style="list-style-type: none"> • Operating -10°C to +50°C • Storage -20°C to +60°C
More features / Applications	<ul style="list-style-type: none"> • Mobile; • Traveling sales; • Retail; • Transportation; • Receipt Printer; • Point of sales; • Healthcare; • Warehousing; • Distribution.
Accessories	<ul style="list-style-type: none"> • Wearable built-in metal belt hook • Neck / shoulder lanyard



DATECS

115 A Tsarigradsko shosse Blvd., Sofia 1784, BULGARIA
tel: +359 (2) 974 00 55; fax: +359 (2) 974 11 00; e-mail: sales@datecs.bg; www.datecs.bg



001