

ODP 1000 by POSLIGNE® EPoS thermal receipt printer



EPoS thermal receipt printer with compact, minimalist, splash-proof design and convenient front receipt printout

Specially designed for point-of-sale and service applications, this thermal receipt printer features a trendy, minimalist style with compact dimensions and design. It is also one of the few machines in its category to feature a front receipt printout, ensuring optimum protection against dust, crumbs

and liquid splashes in tough environments such as kitchens, restaurants, bars, bakeries and the like.

POSLIGNE®'s ODP 1000 has an intense black satin lacquer finish offering modern style and elegance.

ODP 1000 *epos thermal receipt printer*

- Printer features contemporary black satin lacquer finish
- Highly compact, ergonomic design
- Splash-proof receipt printout path located on the front side for enhanced waterproofing protection; perfectly designed for all catering and hospitality sectors.
- Print speed: 160mm/sec
- Integrated dual interface: RS232C serial and USB ports
- Configuration utilities
- All cables supplied



MODEL

ODP 1000

Printing method	thermal
Model	ODP1000
Print method	direct, thermal
Print speed	160mm/sec
Effective Print Width	72mm / 512 dots/line
Characters per line	Font A: 42 columns, 180dpi Font B: 56 columns, 180dpi / 64 columns, 203dpi
Internal memory	64MB
Paper loading	automatic

THERMAL PAPER

Width:	79.5 mm +/- 0.5 mm
Thickness	0.065 - 0.1mm
Max. roll diameter	83mm

CHARACTERS

Alphanumeric	95
Extended graphic	128 x 18 page
International characters	14
Barcodes	UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code
Emulation	ESC/POS* compatible
Drivers	Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS
Sensor	end-of-roll, near end-of-roll, cover open
Till output port(s)	1 dual port (for 2 drawers) - RJ11 6-pin connector
Interfaces	Native USB/RS232 dual interface (non-modifiable)
Power supply	External 24V - 2.5A
Paper cutter	Auto cutter - guillotine type Max. 30 cuts/minute
Cut type	total or partial

OTHER FEATURES

MCBF	35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts
Operating temperature	-20 to +60°C
Operating humidity	10% to 90% (without condensation)
Dimensions (depth x width x height)	164.34 x 135.85 x 110.03mm
Weight	1.4kg

*ESC/POS is a registered trademark of SEIKO EPSON CORP.

Specifications are subject to change without notice