



ODP 200H by POSLIGNE® POS thermal receipt printer



The ODP 200 H is a thermal receipt printer with soft lines, in sync with POSLIGNE® designs.

The **ODP 200 H** type II offers gentle curved lines – far from the straight lines and angles of the traditional printing equipment – a perfect match with the other POSLIGNE® systems and peripherals.

With a speed of 200 mm per second, this is a fast printer with space for paper rolls of up to 102 mm which takes a range of paper widths (standard size is 80 mm). The capacity of its internal memory (8 MB) is also a plus.

In its standard version, the ODP 200 H type II is supplied with a built-in USB interface (A type) - together with an additional Serial interface (DB25 detachable); the latter can be replaced by optional Ethernet, WIFI and Parallel interfaces. The equipment is delivered in one single box with all cables included (USB and Serial).

All POSLIGNE® peripherals are compatible with other EPoS systems available on the market.



ODP 200H II by POSLIGNE®

ODP 200H-II stylish & reliable

- Supplied with an USB interface (A type) and a Serial detachable interface (DB25)
- All necessary cables included (USB and Serial) in the same box
- 8 MB internal memory
- Serial interface can be replaced by WI FI, Ethernet and Parallel
- Automatic paper loading
- ESC/POS compatible
- Rear paper loading for fanfold printing
- End and near end-of roll detection
- End of cut signal (programmable buzzer - 1 to 2 seconds)
- Heavy duty cutter



MODEL ODP 200H

Print method	Thermal
Print speed	200mm/sec
Printhead	72mm: 512 dots
Resolution	180dpi
Characters/line	Font A: 42 column, 180dpi Font B: 56 column, 180dpi
Internal memory	8 MB
Paper loading	Automatic

THERMAL PAPER

Width	80mm standard - adjustable from 50 - 82.5mm
Thickness	0.065 - 0.1mm
Roll diameter	76mm standard - 102mm max.

CHARACTERS

Alphanumeric	95
Graphic characters	128 / 18 pages
International characters	14
Barcodes	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417 (2D), QR code (2D)
Emulation	ESC/POS* compatible
Drivers	Windows (XP, 2000, 2003, Vista, WEPOS, Win 7) / OPOS / Linux / Java POS
Detectors	Roll end & near end
Cashdrawer(s)' ports	1 dual port (for 2 cashdrawers)
Interface	built-in USB (A type) + Serial (detachable DB25)
Optional Interfaces	Parallel, Ethernet, WIFI
Power supply	External, 24V - 2.5A - 110 x 65 x 30mm

PAPER CUTTER

Auto cutter	1 000 000 cuts - guillotine type End of cut signal (programmable buzzer - 1 to 2 seconds)
Cut type	Total or partial cut
Lifespan	1 000 000 cuts
Dimensions (W x D x H)	152 x 222.3 x 156.2mm
Weight (including paper cutter)	1.7kg

*ESC/POS is a registered trademark of SEIKO EPSON CORP.



Pictures & specifications are subject to change without notice