

TRP 100-II by POSLIGNE® EPoS thermal receipt printer



Thermal receipt printer with USB Type A (native) + Serial DB 25 interface

This TRP-100 II offers excellent quality print and quick drop-in easy paper loading.

It is available with USB - A type native + Serial DB25 interfaces; Ethernet and WIFI are optional.

Delivered with all necessary cables, it is one of the lowest-priced quality thermal receipt printer available.

High performance – high quality – low price!

TRP 100-II ready to use

- Easy paper drop-in
- Fast 160mm/sec print
- Thermal roll ø 80mm
- 2D barcode supported
- ESC/POS compatible
- USB (type A) native + Serial DB25 interfaces
(Ethernet 10/100T, Paralell and WIFI (802.11b) are optional)
- Ready to use : all cables supplied!



MODEL

TRP 100-II

Printing method	Direct thermal
Printing speed	160 mm/sec
Printing width	max 72 mm / 512 dots
Resolution	180 dpi x 180 dpi
Characters /line	Font A (12x24) / 42 columns Font B (9x17) / 56 columns
Paper loading	Easy paper drop in
P A P E R	T H E R M A L
Width	50mm - 82.5mm
Thickness	0.06 – 0.09
Roll diameter	Max 83mm
C H A R A C T E R S E T	
Alphanumeric	95
Extended graphics	128 x 18 pages (1 space /page)
International characters	14
Barcodes	UPC-A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D: PDF 417, QR Code
Emulation	ESC/POS* compatible
Sensors	end of paper, paper low sensor, cover open sensor
Drawer port	1 double port (for 2 cash drawers)
Interfaces	USB (type A) native + Serial DB25 interfaces
Interfaces optionals	Paralell, Ethernet and WIFI
Drivers	Windows Driver (7, XP, 2000, 2003, Vista, XP Embedded) Linux, OPOS, WEPOS, JavaPOS
A U T O C U T T E R	
MTBF	1.5 million – guillotine type
Cutting method	total or partial cut
Power supply	External 24V
Colour type	graphite grey, pearl white
Dimensions (LxDxH)	152 x 202 x 150 mm
Weight	1.7 kg

*ESC/POS is a registered trademark of SEIKO EPSON CORP.

