

SEDONA 58



THERMAL RECEIPT POS PRINTER

- Outstanding functions
- Strong stability
- Avoid order missing



SPECIFICATIONS

Printing method: Direct thermal
Printing speed: 90 mm/s

Paper width: 57.5 + 0.5mm
Paper diameter: 60mm
Paper thickness: 57.5 + 0.5mm
Column capacity: 384 dots/line
Line space: 37mm (changeable using commands)
Character size: ANK, Font A: 12x24 dot, Font B: 9x17 dots

Bar code: UPC-A/UPDC-E/JAN13 (EAN13) JAN8(EAN8) / CODABAR/ ITF/CODE39/CODE93/CODE128
Code page: PC347 (Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek Hebrew, East Europe, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, Latvian, Arabic, PT151 (1251)

NV FLASH: 64k Bytes
Input buffer: 32K Bytes
Power supply: DC 12V/ 2.6A
Cash drawer control: DC 12V/ 1A
Interface: Parallel/Serial/USB/Lan
Reliability: Printing head life: 50 km
Working environment: Temperature (0-45°C)
humidity(0-80%)
Storage environment: Temperature(-10-60°C)
humidity(0-80%)

Drivers: Win 9X/ Win ME/ Win 2000/ Win 2003/
Win NT/ Win XP/ Win Vista/ Win 7x/
Win 8/ Win 8.1 / Linux
Command: Compatible with ESC/POS

Gross wight: 0.94 kg
Dimension: 235x 145x 125mm (Dx WX H)

APPLICATION



Market



Catering



Store



Post

DRIVER

