

POSLIGNE®

ePOS to match  
your store decor

# OLC 15

POINT OF SALE TOUCHSCREEN



Elegant, stylish  
touchscreen  
designed especially  
for the world  
of retail

Fully in keeping with the POSLIGNE® spirit, the OLC 15 is the first point-of-sale touchscreen to feature interchangeable colour schemes. The unique modular "Clip'n Color" system, with clips in different hues, enables the device to be matched to any sales environment and maintain its visual identity.

Its refined, elegant lines, strikingly original profile and overall appearance make this

touchscreen one of a kind in the POS IT market. Retail users and staff will love its state-of-the-art design - equally attractive when viewed from in front, behind, and in profile - and so will customers paying for their purchases.

All POSLIGNE® peripherals are compatible with other POS systems available on the market.

OLC 15 by POSLIGNE®

# OLC 15: COMPACT AND STYLISH

## Clip'n Color

Add a touch of colour to your OLC 15 with our clever clip system!

These modular, interchangeable, clip-on, clip-off parts made from polycarbonate are easy to fit and remove on the front, sides and customer display, so the OLC 15 can blend into its environment, changing its colour as the mood takes you!

### OLC 15 - key advantages:

- Slimline design and compact footprint free up plenty of room on the sales counter.
- Power supply unit incorporated into the base
- Tilting customer display
- Front-facing USB port
- Base supplied in 2 colours (pearl and graphite), plus 8 interchangeable colour clips
- The OLC15 is the natural companion to the Poséo Retail PC



#### colours of the system base

- pearl
- graphite

#### colours of the clips

- tonic orange
- carmine red
- pure white
- spice yellow
- soft blue
- indigo blue
- metal grey
- racing green

#### MODEL

#### OLC 15

Touchscreen type	15" resistive touchscreen pad (USB interface)
LCD technology	TFT (liquid crystal display) LCD panel / display
Brightness	up to 250cd/sqm
Resolution	1024 x 768
Contrast	400 : 1
Tilt angle	0 – 70°

#### S C R E E N

OSD buttons	1 off/on button, 1 menu button, 4 screen setting buttons
On/off LED	1
USB	1 on front face

#### C O N N E C T I O N S

PS2	2 x PS2 (system input + keyboard output)
Serial/Com Port	1 RJ 45
USB	1 touchscreen / customer display
Audio	1 input / output
DC Jack	1 (12V)
Integrated power supply	30W (12V / 2.5A)
VGA	1

#### E N V I R O N M E N T

Safety / EMC	FCC Class A, CE, LVD
Operating temperature	+5° / +35°C
Storage temperature	-10° / +60°C
Humidity rating (in operation)	20% ~ 85% (RH without condensation)
Humidity rating (in storage)	5% ~ 90% (RH without condensation)
Customer display	VFD Display (USB interface) 2 lines x 20 characters
Dimensions (W x D x H)	419 x 310 x 253 (up to 332)mm
Weight	6kg

#### O P T I O N S

Magnetic card reader	3-track (RS 232 or keyboard interface)
Optional internal loudspeakers	2 x 2W



Optional card/Dallas reader or RFID reader



Integrated power supply adapter