



1717L 17" LCD Desktop Touchmonitor

Rugged, flexible, space-saving

The Elo Touch Solutions 1717L is well-suited to meet the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions including:

- Point-of-sale (POS)
- Point-of-service
- Loyalty systems
- Countertop kiosk point-of-information
- Back office solutions integrating labor management and inventory analysis
- Shelf-level/countertop interactive digital signage displays

Available with a choice of two zero-bezel touchscreen technologies, iTouch surface acoustic wave or AccuTouch resistive, the 1717L provides stable, "drift-free" operation with excellent image clarity, resolution, and light transmission—for an accurate touch response and vivid images!

Features and Benefits

- Choice of two leading Elo zero-bezel touchscreen technologies for a seamless, easy to-clean glass-to-edge design:
 - iTouch surface acoustic wave
 - Zero-bezel AccuTouch resistive
- 5:4 aspect ratio panel
- USB touch controller, VGA port
- LED backlighting allows for state-of-the-art slim design with lower power consumption than CCFL
- Removable base and mounting features including VESA, wall- and arm-mounting options for installation flexibility and mounting holes on base for table-top security
- Optional peripherals include field-installable 3-stripe Magnetic Stripe Reader (MSR), Rear Facing Customer Display (RFCD) and various display stands
- Digital on-screen display (OSD) and controls on the side with lock-out function for public use



1717L 17" LCD Desktop Touchmonitor

Computer Specifications

Model	1717L
Color	Black or white
Active Display Area	13.3" x 10.6" (337.9mm x 270.3mm)
Dimensions* (without stand and packaging)	15.42" x 7.53" x 14.18" (391.9mm x 191.3mm x 360.2mm) max
LCD Technology	Active matrix TFT LCD
Diagonal Size	17"
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Video Source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Mounting Options*	VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Preset Video Timings	640 x 480 60Hz,75Hz; 720 x 400 70Hz; 800 x 600 56, 60Hz,75Hz; 1024 x 768 60Hz,75Hz; 1280x1024 60Hz,75Hz
Number of Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits; with iTouch: 225 nits; with AccuTouch: 200 nits
Response Time (Tr + Tf) (typical)	30ms
Viewing Angle (typical)	Horizontal: 170°; Vertical: 160°
Contrast Ratio (typical)	800:1
Video	Analog VGA on Female DE-15 connector; Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor input power connector: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5%. Note: This monitor is sold with an AC-DC power adapter. Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor + AC/DC adapter): 21W; SLEEP (monitor + AC/DC adapter): 1.1W; OFF (monitor + AC/DC adapter): 1.0W
Weight (with stand)	Unpackaged: 12.1 lbs (5.5kg); Packaged: 16.5 lbs (7.5kg)
Shipping Dimensions	18.5" x 16.7" x 8.89" (471mm x 426mm x 226mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; BSMI Mark; UL, FCC; CB; RoHS, China RoHS, WEEE, IMERC
Warranty	3 years
MTBF	50,000 hours demonstrated

*See dimensional drawings for details

For updated specifications and more information, please visit www.elotouch.com.

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800

Fax 1-650-361-4722

customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00

Fax +32 (0)16 35 21 01

elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161

Fax +81 (45) 478-2180

www.tps.co.jp

Latin America

Tel 786-923-0251

Fax 305-931-0124

www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and iTouch are trademarks of Elo Touch Solutions, Inc.
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 10/12

www.elotouch.com

