

Ultra-compact & fully adjustable EPOS system



Small and reliable, **ninô** by AURES is a compact and fully adjustable EPOS.

With its sleek modern appearance and capabilities, **ninô** is an ultra-compact, fully adjustable EPOS, with the specificity of being *able to fold flat*; it is *perfectly suited for most retail and point of sale sectors*.

It has a 14 inch 16:9 format style touch-screen and is designed to be no bigger than a small desktop, with full EPOS functionalities. Thanks to its completely flexible and adjustable swing arm, which is attached to the die-cast aluminium base, it can be folded *flat* or adjusted to all viewing angles from *flat to 90°*.

This means it can be used "*flat*" like a console, on its base, or mounted on a wall or pole (*several mounting accessories, as well as VESA fixings, are available*).

Fanless, it is perfect for harsh environments and always in tune with the new environmental standards (*low energy consumption and small carbon footprint*).

It is the ideal companion for all pop-up stores and shops, for take away food & non-food specialists, including food & catering trucks, mobile canteens, etc.



ninô small, compact & smart

- Intel Cedar View D2550 processor
- Edgeless flat touchscreen
- Small, ultra compact EPOS – able to fold flat
- 2.5" HDD or SSD (in option)
- Base fully adjustable from flat to 90°
- 4 serial ports, 4 USB ports
- Display Port with HDMI support
- +12 V output for peripheral power supply
- Low power consumption
- Small foot print
- Manifold system: base, pole or wall mounting options



MODEL

ninô

Processor	Intel Atom Cedar View D2550
Chipset	NM10
Memory	DDR3 SODIMM 2GB in standard - up to 4GB (2 sockets)
HDD or SSD	Quick change, 2.5" SATA (or optional SSD)
LCD	14" TFT (1366 x 768) – LED back light
Touchscreen	'True Flat Resistive' & edgeless (zero bezel)
Brightness	220 cd/m2 with auto dim

I / O P O R T S

Serial	4 x serial ports with + 12V power option
USB	4 x USB 2.0 ports
Power out	+ 12 volts for peripheral power
LAN	10/100/1000 Base-T
2nd Display	Display Port with support for HDMI, DVI et VGA (with adaptor)
Cash drawer	1 x 12 V or 24 V
Audio/sound	internal speakers and combo headset + mic jac
Power input	19VDC from 65W power adaptor mounted in base
Mini-PCI Express	1 internal mini PCI Express slot (for WIFI)

E N V I R O N M E N T

EMI	CE/FCC Class A
Safety operating	LVD, external adaptor UL c/us, CE, TUV, others
Temperature	0 – 40° C
Spill resistant	
Compatible O/S	Windows 7, Windows 7 Embedded, POS Ready 7, XP, POSReady 2009, XP Embedded Standard, Compact Windows 7
OPOS	OPOS drivers for MSR, customer display, cash drawer
Dimensions (WxDxH)	folded - 361 x 254 x 81mm At 55° viewing angle - 361 x 232 x 255mm
Weight	3.7kg
Standard colour	grey

O P T I O N S

MSR	3 track ISO, OPOS support
Dallas key reader	mounts to any of 4 mounting points
Fingerprint reader	mounts to any of 4 mounting points
Customer display	20 characters x 2 lines VFD (rear display)
2nd screen	10.1" - 16:9 format - 1024 x 600 TFT LED
WI FI	802.11 b/g/n, internal
Optional colours	available upon request - please contact us



Slim Design

Specifications are subject to change without notice- © AURES 2013