

AURES[®]



sango



sango
irresistible epos

sango

sango - from the **AURES** Group - is an exclusive design concept of integrated EPOS: one of its many unique features is to completely free-up the space under the touch screen.

With no intrusive stand, it soars effortlessly, as if weightless, offering and revealing a space traditionally occupied by the central unit.

Elegantly suspended on its offset cast aluminium arm, the real *exo-skeleton* of the EPOS terminal and support for its technological core (CPU), **sango** combines minimalist lines, ergonomics and low power consumption.

Stable and rigid, its thin metal base (*a natural extension of the slender and beautifully-designed arm*) acts as a *heat sink*.

sango will adapt to the technology requirements of all users: 4 types of processors are available, to suit their needs, as well as a range of connection options. The flat LED touch monitor, with an edgeless display surface, is offered in *resistive and/or projected capacitive* versions.

Enhanced by the finish of the polycarbonate, **sango's** seven interchangeable colours (*White, Black, Red, Blue, Orange, Grey & Cassis*) fit into the revolution line started by **AURES** in 2005 and provide the final touch for the brand image and visual identity of all points of sale and points of service.

Benefits & technical specifications

Free space under the screen

Touch screen

Thin, flat, resistive (ELO Touch), or projected capacitive touch-panel, tilts to horizontal (90°)

High quality display

15" LED-backlit LCD - 300 cd/m²

Fanless EPOS terminal (no ventilation) with low power consumption

7 colours (interchangeable polycarbonate parts) White, Black, Red, Blue, Orange, Grey, Cassis.

Processors

INTEL Ivy Bridge i5 - 3337U
INTEL Ivy Bridge i3 - 3217UE
INTEL Ivy Bridge 1047 UE
INTEL Cedarview D2550

INTEL HD Graphics 4000 core (i5 / i3)

Chipset : INTEL HM76 or NM10

Memory

SO-DIMM DDR3 x1 - up to 4GB (1067 MHz)
SO-DIMM DDR3 x1 - up to 8GB (1333/1666 MHz)

Flash memory : SSD as option

HDD: 1 x 2.5" (rack-mounted)

Connections

Front: 2 x USB3.0 / or 2 x USB2.0
Rear: 2 x USB2.0 + 2 x USB3.0 / or 4 x USB2.0

Serial / COM ports

4 x RJ45 (including 3 powered)
1 x LAN (10/100/1000)
1 x cash drawer port
1 x display port (2nd screen)

External power supply

65W (19V/4.7A adaptor)

Net weight: 8.70kg (not including power supply or customer display)

Dimensions: L x H x D: 410 x 400 x 380mm (working position – tilted at 45°)

Compatible OS: Windows XP Pro, Windows POSReady 2009, Windows 7 Pro, Windows POSReady 7, Linux.

Associated peripherals

Readers

Cards
Dallas keys
Addimat keys
1D barcodes
2D barcodes

ODP 333 Receipt printer

3S 333 Cash drawer

Graphic customer displays

Integrated or external - high readability

2nd screen : at the back of the system, (integrated) or standalone (external)



AURES®



www.aures.com

