

POSLIGNE®

ePOS to match
your store decor

POSÉO 5100

RETAIL PC RANGE



A reliable
PC platform
for all retail
applications and
environments

Designed especially for the world of retail, Poséo is a PC platform dedicated to the POS technology market.

Featuring compact dimensions, this system is sturdy, safe, reliable, long-lasting and easy to maintain, and is at home in both "front office" environments (cash desk) and in the "back office" (where it can be used as a server, for example).

When used with a touchscreen such as POSLIGNE®'s OLC 15, Poséo functions as the nerve centre of an high-performance point-of-sale system.

The Poséo PC is built on a 1.6mm-thick reinforced steel baseframe, ensuring optimum solidity. It operates with a 2.5 GHZ processor and has a 2 GB DDR2 RAM memory.

POSÉO: PERFORMANCE FOR RETAIL

Poséo - key advantages:

- Slimline design and compact footprint free up plenty of room on the sales counter.
- Sturdy enough for the most demanding retail applications
- High performance
- Multiple dedicated connections
- Optimised for easy maintenance
- Long-lasting components



Poséo

ODP 200

OLC 15

MODEL

POSÉO 5100

Motherboard	B89
Processor	INTEL SK478 CPU M Celeron 2,5GHz
Chipsets	INTEL 852 GM + ICH4
RAM	512 MB up to 2GB DDR RAM, 2 RAM-DIMM

STORAGE

Hard disk drive	1 x HDD-IDE de 3,5" (2 disk available)
-----------------	--

FRONT CONNECTIONS

USB 2.0	1 x USB
On/off button	
Key lock	

REAR PORTS

Keyboard	1
USB 2.0	4
Series/COM	6 (COM1/COM2/COM3/COM4/COM5/COM6)
Cashdrawer ports	1 x RJ 11 (12V / 24V)
VGA	1 x DB 15F
Audio	1 input
10/100 LAN	1
Parallel (printer)	1 x DB 25F
24V port	1 (printer)
12V port	1 (VFD customer display)

OPTIONAL PORTS

12V USB Retail	2
24V USB Retail	1
5V USB Retail	1
USB 2.0	4
Serial/COM	2 x RS232 + 2 USB 2.0

ENVIRONMENT

Power supply	integrated 230W
Safety / EMC	FCC Class A / CE / LVDT
Operating temperature	+5° / +35°C
Storage temperature	-10° / +60°C
Humidity rating (in operation)	20% ~ 85% (RH without condensation)
Humidity rating (in storage)	5% ~ 90% (RH without condensation)
Dimensions (W x D x H)	270 x 335 x 120mm
Weight	7kg net – 8kg gross
Operating systems	Windows XP, WEPOS, Vista, XP Embedded, Windows 2000 Professional embedded, Linux



Optimum connection capabilities



Motherboard in steel housing



2 disk drives

Specifications are subject to change without notice