



XIAMEN RONGTA TECHNOLOGY CO., LTD.

ADD:No.1501, C1 Building, Wanda Plaza, No.3 Jinzhong Road, Huli Area, Xiamen, China 361006

TEL:0086-592-5030657

FAX:0086-592-5659169

M.Phone: 0086-1355-9497693

Contact Person: Ana Woo


E-MAIL: rt11@rongtatech.com

Skype:rongtatech11

Website: www.rongtatech.com

Item Name:	3" Thermal Portable Printer RPP300
Product Photo:	
Price(FOB):	RPP300BU(Bluetooth+USB): USD85/unit
	RPP300WU(Wifi+USB): USD97/unit
	RPP300BWU(Bluetooth+Wifi+USB): USD105/unit
Printing way:	Thermal Line printing
Paper width:	80mm
Printing width:	72 mm
Resolution:	203dpi(8 dot/mm)
Printing speed:	75 mm/s (max)
Dot /line:	576 dots/line
Print Font	ASCII Font A: 12×24/ASCII Font B: 9×17/Chinese: 24×24
Characters per Line	Font A: 48/Font B: 64/Chinese: 24
Rolling paper Diameter:	∅ 40(max)X80mm
Paper feeding method:	Easy paper loading
Barcode type:	CODE39/EAN-13/EAN-8/CODABAR/CODE93/ITF /QR/PDF417
MCBF:	5 Million Lines
Print head lifespan:	50 km
Interface:	Bluetooth(BT4.0&BLE)/WiFi/USB/RS232
Paper out alarm:	Support
Printing Command:	ESC/POS
Battery:	2000 mAh rechargeable li-ion battery
	lifespan is more than 500 times
	Continuously working for 3 hours or 100m
	4-6 hours' charging time
Power Supply:	USB/Power adapter/mobile power charging
Power alarm:	Battery need to be charged or changed when battery light turns off and red light turns on
Dimension(LxWxH):	113×103×45(mm)
Weight:	335g (including the paper roll and battery)
Environment parameters:	Working temperature: -10℃ ~ 50℃
	Working humidity: 20% ~ 85%
	Storing temperature : -20℃ ~ 70℃
	Storing humidity: 5% ~ 95%

Item Name:	2" Thermal Portable Printer RPP200
Product Photo:	
Price(FOB):	RPP200BU(Bluetooth+USB): USD65/unit
	RPP200WU(Wifi+USB): USD77/unit
	RPP200BWU(Bluetooth+Wifi+USB): USD85/unit
Printing way:	Thermal sensitive line dot method
Paper width:	56mm
Valid printing width:	48 mm
Paper thickness:	60 ~ 80μm
Rolling paper Diameter:	∅ 40(max)X58mm
Paper feeding method:	Easy paper loading
Resolution:	8 dot/mm (203 dpi)
Dot /line:	384 dots/line
Printing speed:	80 mm/s (max)
Print Font	ASCII Font A: 12×24/ASCII Font B: 9×24/Chinese: 24×24
Characters per Line	Font A: 32/Font B: 42/Chinese: 16
MCBF:	5 Million Lines
Print head lifespan:	50 km
Interface:	Bluetooth(BT4.0&BLE)/WiFi/USB/RS232
Barcode type:	CODE39/EAN-13/EAN-8/CODABAR/CODE93/ITF/QR/PDF417
Paper sensor:	Support
Printing Command:	ESC/POS
Battery:	<ol style="list-style-type: none"> 1. 1350 mAh rechargeable li-ion battery 2. Continuously working for 3 hours or 100m 3. 3-5 hours' charging time 4. lifespan is more than 500 times.
Power alarm:	Exclusive power indication light turn off and red light flashes when the printer is running out of power. Then it must be charged or changed the battery.
Power Supply:	USB/Power adapter/mobile power charging
Environment parameters:	<p>Working temperature: -10℃ ~ 50℃</p> <p>Working humidity: 20% ~ 85%</p> <p>Storing temperature : -20℃ ~ 70℃</p> <p>Storing humidity: 5% ~ 95%</p>
Outer dimension(LxWxH):	112*79*45mm
Weight:	110g (including the paper roll and battery)

Item Name:	2" Thermal Portable Printer RPP-02
Product Photo:	
Price(FOB):	USD39/Unit
Printing way:	Thermal sensitive line dot method
Paper width:	56mm
Paper thickness:	60 ~ 80μm
Valid printing width:	48 mm
Resolution:	8 dot/mm (230 dpi)
Dot /line:	384 dots
Printing speed:	50-80 mm/s
Printing content:	Support any language
Outer dimension:	102*108*50mm
Weight:	340g
Rolling paper Diameter:	≤30.5mm
Interface:	Original IR(RAW_IR), VIR, IrDA (IrCOMM) RS232 port, blue tooth, USB interfaces varied with different models.
Environment parameters:	Working temperature: -10℃ ~ 50℃ Working humidity: 20% ~ 85% Storing temperature : -20℃ ~ 70℃ Storing humidity: 5% ~ 95%
Paper feeding method:	Easy paper loading
Mark position:	Detecting mark position
Paper sensor:	LED indicator flashes when come to paper end meanwhile alarm.
Printing Command:	ESC/POS compatible with commands set
Power:	1500 mAh rechargeable li-ion battery
Power alarm:	Indicator flashes when printer run out of power and give out two short hoots. When running out of power, buzze will give out interval warning to indicate charging.